

PRODUCT DATASHEET

Last update: 20.9.2018

Product: Nitro Dispenser 2-Tap

Model: 2018-CA2-01

Electrical & refrigerant

Power supply	230 V / 50 Hz / AC ~
Wattage / amperage	334 W / 1,45 A
Refrigerant / amount	HFC R-134a / 68 g
Cooler type	dry
Climatic class	N



Device connections

Product In	2 x Linktech coupler – socket
Nitro-Port	N/A
Power cable	Firmly connected; 1.5 m
Plug	Schuko CEE-7/7 plug

Features

Jet-nozzle spout	2 x yes
Gas amount control	2 x yes (default gas flow setup: 15-20 l/h)
Nitro-Switch	2 x Nitro ON/OFF switch
Micro airfilter	yes (0,1 µm)
Nitro source	air
Temperature setup	4.5 – 5.5°C (at level 7 on front scale)
Temperature control	yes (range 5°C – 17°C)
Flowrate	2 x 0.6 l/min (2 hole disc)
Cooled liquid buffer	0.5 l
Nonstop dispense cooling	Δ 7°C (at 0.6 l/min)

Accessories box

Drip tray	yes
Inlet strainer	2 x yes (for particles > 0.1 mm)
Detergent	2 packs of Thonhauser DESANA MAX CL detergent
5-hole disc	N/A
Intake Product Line	2 x Linktech coupler – plug; 3/8" hose 1.5 m; strainer; ball-lock coupler

Other

Customs code	84388091
Warranty	2 years

Available options

- Cold temperature setup (-1 °C)
- Individual branding through magnetic foil
- 5l Canisters

Weight & Dimensions

Net / gross weight: 20.5 kg / 23.0 kg
Dimension dispenser: 51.5 x 18.0 x 55.0 cm (H x W x D)

Packaging

Single Box 46.0 x 25.0 x 59.0 cm (H x W x D) | 23.0 kg
Euro-Palette (120x80 cm) 3 layers
6 boxes per layer, 18 boxes per palette
Size 120 x 80 x 200 cm
net weight 369 kg
gross weight 429 kg