



PRODUCT DATASHEET

Nitro-Dispenser Ketel1 / ND-20-01-01 DI / 230V/50HZ~

Taps	1 Tap
Model	ND-20-01-01 DI
Picture	
Beverages	Espresso-Martini, Coffee-Cocktails, Cold-Brew-Coffee
Electrical & refrigerant	
Power supply	220 – 240 V~ / 50 Hz ~
Wattage / amperage	408 W / 1,7 A
Refrigerant / amount	 R290, 47g Propane is an extremely flammable gas
Electrical connection	C14 socket
Power cable	Country specific plug with C13 plug
Cooler type	dry
Climatic class	N
Accessories	
5l cleaning or product canister with CPC socket	2 x
Intake hose with strainer and CPC coupler	2 x
Inlet strainer for particles > 0.1 mm	2 x
Drip tray	1 x
Detergent	1 jar (566 g) of ONE-PRO cleaner from URNEX

Features	
Nitrogen source	Filtered compressed air (78% nitrogen)
Jet Nozzle Mono with spray crowns flowrate: 0.6 l (20 oz)/min	1 x
Nitro toggle switch to switch between Nitro and non-Nitro	1 x
Foam level control	No adjustment – default factory setup
Particle air-filter	Yes
Nitro-Port to connect nitrogen bottles	No
Temperature setup	For cleaning use Level 4 on the front scale For coldest temperature use Level 7 on the front scale
Liquid volume inside dispenser	1 x 370 ml (12.5 oz)
Cooling effect during nonstop dispense	$\Delta 7,0^{\circ}\text{C}$ (at 0.6 l/min)
Continuous (non-stop) dispense is only possible until an ambient temperature of 30°C. Between 30 and 35°C non-stop dispensing is possible up to 30 min. Then the dispenser needs a recovery break of 15 min to cool down again.	
Device connections	
Product inlet	1 x CPC coupler 3/8" hose
Others	
Noise emission level	≤ 64 dB
Warranty	1 year
Weight & dimensions	
Net / gross weight	20.9 kg / 23.3 kg
Dispenser dimensions (H x W x D) including tap handle	53.0 x 19.5 x 55.0 cm
Packaging dimensions (H x W x D)	65.0 x 25.5 x 59.0 cm

